MGEN 5	600					
Power Ratings		Standby		Prime		
		kW	kVA	kW	kVA	
Diesel		400.0	500.0	400.0	500.0	
ENGINE SPECIFICATION		ENGINE ELECTRICAL S	YSTEM:			
INGINE SPECIFICATION	Damlier	Starting motor voltage		24DCV		
Nodel	Series 60	Charger Amps		55		
missions	US EPA Certified	Battery Ampere Hours		200AH/1000CCA		
ngine speed (rpm)	1800	ALTERNATOR:				
1ax. HP Power 1800 rpm	515 ISO3046	Configuration		4 Pole 3 Phase/NEMA Class H Insulation		
ylinder arrangement	I-6	Frequency		60HZ		
ombustion system	Compression	Voltage regulation		Automatic		
spiration	Turbocharged	No load to full load voltage regulation		Digital		
ngine type	Diesel	Coupling		Direct		
Jel	Diesel	Bearing		Single		
lumber of Cylinders	6	Manufacturer		Marathon		
isplacement (liters)	14.0	Model		431CSL6206		
ore and Stroke (mm)	106x168	Load acceptance		100% Single Step		
ooling	Coil and Tube	Compliance		UL		
overnor	Integrated Isochrones	Construction		Single Bearing Marine Insulation		
tarting aids	None FUEL CONSUMPTION: Ibs/hour NG Standby rati			ting 1800 LBS/HP/HR		
ompression ratio	17:1	100%		198		
ir cleaner type	Dry	75%		187		
xhaust Configuration	EPA Tier 3	50%		115		
uel switch	NA	25%		85		
COOLING SYSTEM FOR OPERATING	AT 120º AMBIENT:	CONTROL PANEL SPEC	CIFICATIONS:			
ooling System	Radiator CAC Combo	Model		Basler 2020HD		
ngine Coolant Capacity: Gallons	TBD	Microprocessor based		Yes		
an	Pusher	Operating power		24V		
adiator	CPSSI	Consumption				
oling air flow - @ 1" Static H2O Pressure and 125F 24,579		Remote communication capabi	Remote communication capability		Yes	
UBRICATING SYSTEM:		ENCLOSURE AND ARR	ANGEMENT OF COM	PLETE ASSEMBLY:		
tal lubricating capacity quarts (Liter) 129/122 Coupl		Coupling	oupling		Flexible	
ecommended lubricating oil grade	Low Ash Diesel Engine oil	Enclosure		Yes		
il Pressure Minimum 1800RPM –(bars)	3.24	Base arrangement		Generator and Co	ntainment	
1aximum Allowable Oil Temperature (C)	110C	Spill containment		100%		
KEY DIME	ENSIONS AND WEIGHT					
Description (inches)	Height					
Open Set						
Enclosed Set	119"			CENTRAL - HOM		
Trailer mounted						
	Width	Length				
W1						
W2	96"	252"				
W3				_		
Weights	Dry weight lbs	Wet Weight lbs	Sound dBA			
Open Set	NA	NA	NA NA Q			
Enclosed Set	19865	20760				
Trailer mounted 21605		22500	81			
		_				